

AERO-GEL



DANGER:

Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. May cause damage to organs through prolonged or repeated exposure. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container in accordance with local/regional/national/international regulations.

FIRST AID:

IF SWALLOWED: Immediately call a poison center/doctor. Do NOT induce vomiting. **IF ON SKIN:** Wash with plenty of water. Get medical advice/attention if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. **IF INHALED:** Move to fresh air. Call a physician if symptoms develop or persist. **IF IN EYES:** Rinse with water. Get medical attention if irritation develops and persists.

NOT FOR SALE OR DISTRIBUTION IN CA, UT, OTC AND LADCO STATES.

CONTAINS/CAS NUMBER:

d-Limonene (5989-27-5), Naphtha (petroleum), Heavy Alkylate (64741-65-7), Propane (74-98-6), Synthetic Amorphous Silica (112945-52-5), and 2-Butoxyethanol (111-76-2).

Distributed By: Total Solutions®
PO Box 240014 • Milwaukee, WI 53224 • 1-800-743-6417

TOTAL SOLUTIONS®

AUTOMOTIVE

AERO-GEL

Citrus-Based Gel

- WITH THE POWER OF D-LIMONENE
- NSF REGISTERED

KEEP OUT OF REACH OF CHILDREN

DANGER

EXTREMELY FLAMMABLE.

HARMFUL OR FATAL IF SWALLOWED.

EYE AND SKIN IRRITANT.

CONTENTS UNDER PRESSURE.

Read carefully other cautions on back panel.

NET WT: 14 OZ (397 g)

Distributed By: Total Solutions®
PO Box 240014 • Milwaukee, WI 53224 • 1-800-743-6417

DESCRIPTION

This product combines d-Limonene with the convenience of an aerosol. The clinging gel adheres to vertical and irregular surfaces. It removes the most stubborn deposits so they can be flushed away with water quickly and easily.

This heavy duty gel removes tar, pitch, asphalt, roofing compounds from tools, forms and brick, stone and masonry surfaces. It quickly strips thick and stubborn deposits from asphalt spreaders, rollers and also heating pots, paddles, buckets, brooms, shovels and other tools.

DIRECTIONS

SHAKE WELL BEFORE USING.

Remove cap and spray evenly over the entire surface. Allow to work for 1-2 minutes. Flush away with water. Repeat as necessary. Do NOT apply to plastic parts.

Cautions: Use with adequate ventilation. Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

KEEP OUT OF REACH OF CHILDREN.

HMS® RATINGS:

HEALTH - 2, FLAMMABILITY - 4, PHYSICAL HAZARD- 2, PERSONAL PROTECTION - X.

See Safety Data Sheet for complete safety information. 24 HOUR MEDICAL EMERGENCY 1-866-836-8855
CONTAINS NO OZONE DEPLETING CHEMICALS!

NSF

Nonfood Compounds
Program Listed C1
Registration No. 135367

8388.061818