

## DISPOSAL

Offer empty container for recycling. If recycling is not available, discard container in trash.

**⚠ WARNING:** This product can expose you to ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

# TOTAL SOLUTIONS<sup>®</sup>

SPECIALTY PRODUCTS

## SHIELD

### Stone, Concrete and Wood Surface Sealer

- WATER-BASED PENETRANT AND SEALER
- MAINTAINS SURFACES' NATURAL LOOK
- PROTECTS AGAINST WATER, OIL, DIRT AND GREASE
- PROTECTS AGAINST STAINS AND OTHER DAMAGE
- FOR USE INDOORS AND OUTDOORS

**KEEP OUT OF REACH OF CHILDREN**

**NET CONTENTS:** One Gallon (128 fl. oz.)

Manufactured By: Total Solutions<sup>®</sup>

PO Box 240014 • Milwaukee, WI 53224 • 1-800-743-6417



Please Recycle.

## DESCRIPTION

This water-based, high grade, one step, multi-purpose sealer penetrates and bonds to provide exceptional protection against water, stains, dirt, grease and oil. Use on concrete, wood, unglazed stone, grout, ceramic, marble, limestone, travertine, quarry tile, flagstone, terrazzo, granite, masonry, brick, slate, and stucco surfaces.

## DIRECTIONS

**BEFORE APPLYING:** Make sure that the surface is completely clean and dry. Test on a inconspicuous area before applying. Close off area with wet floor signs.

**APPLICATION:** Apply to a clean dry surface that is free of other coatings. Do not dilute product. Apply using a brush sponge, medium nap roller, or low pressure sprayer.

**CURING:** The polymer will be cured as soon as the surface is dry. Check to determine that curing is complete by placing a small droplet of water on the surface. If the water beads up, the sealer has satisfactorily cured.

**COVERAGE:** 250-500 square feet per gallon depending on the porosity of the surface. Two coats are recommended.

**OPTIMUM APPLICATION TEMPERATURE:** 50-90°F. The durability of the protection can be increased by heating the area after applying.

## NFPA<sup>®</sup> RATINGS

Health: 1; Flammability: 0; Reactivity: 0

**CONTAINS/CAS NUMBER:** Water/7732-18-5; Fluoropolymer/Proprietary; 2-methylpentane-2,4-diol/107-41-5; 2-methyl-2H-isothiazol-3-one/2682-20-4; 1,2-benzisothiazol-3(2H)-one/2634-33-5

*For industrial and commercial use only.  
For additional information, see Safety Data Sheet.*

0123.020518