



## DANGER

Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause an allergic skin reaction. Causes eye irritation. May cause respiratory irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.

**IF SWALLOWED:** Immediately call a doctor, a POISON CENTER. Do NOT induce vomiting. **IF ON SKIN (OR HAIR):** Take off immediately all contaminated clothing. Rinse skin with water/shower. **If skin irritation or rash occurs:** Get medical advice/attention. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **If eye irritation persists:** Get medical advice/attention. **If exposed or concerned:** Get medical advice/attention. Get medical advice/attention if you feel unwell.

**In case of fire:** Use carbon dioxide (CO<sub>2</sub>), dry extinguishing powder, foam to extinguish.

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

**⚠️ WARNING:** This product can expose you to benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## NFPA® RATINGS

Health: 3; Flammability: 2; Reactivity: 0

## CONTAINS/CAS NUMBER:

Distillates (petroleum), hydrotreated light/64742-47-8; Proprietary Epoxy Resin/Mixture; Medium Aliphatic Solvent Naphtha (petroleum)/ 64742-88-7; Mixed xylenes/1330-20-7; Ethyl Benzene/100-41-4; Light Aromatic Solvent Naphtha (petroleum)/ 64742-95-6; Cobalt Carboxylate/136-52-7; Cumene/98-82-8; Aliphatic Petroleum Distillates/64742-48-9; Mineral Spirits/8052-41-3; 1,2,4-Trimethylbenzene/95-63-6

*For industrial and commercial use only.  
For additional information, see Safety Data Sheet.*

# TOTAL SOLUTIONS®

RESILIENT FLOOR CARE

## CONCRETE SEAL

- PENETRATES AND SEALS CONCRETE FLOORS
- EPOXY ESTER RESIN
- PROTECTS FLOORS FROM THE EFFECTS OF TRAFFIC AND CHEMICALS

## KEEP OUT OF REACH OF CHILDREN

**NET CONTENTS:** One Gallon (128 fl. oz.)

Manufactured By: Total Solutions® • 1-800-743-6417  
PO Box 240014 • Milwaukee, WI 53224 • [athea.com](http://athea.com)

**DESCRIPTION:** This specially-formulated epoxy ester resin sealer is designed to penetrate the surface of concrete floors. It dries to a durable, chemical-resistant finish capable of withstanding heavy usage.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, open flames, sparks. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof lighting, electrical equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

Do not breathe mist, spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear eye protection, protective clothing, protective gloves. Take off contaminated clothing and wash it before reuse.

**DIRECTIONS:** New concrete floors must be cured a minimum of 90 days prior to sealing. Clean the floor thoroughly with detergent and water, rinse, and allow to dry for at least 2 hours. Etch the floor using 1 part concrete etcher and cleaner in 5 parts of water. This process neutralizes the alkalinity of the concrete, aiding in the penetration of the surface for better curing and adherence.

Apply this product with a lamb's wool applicator. Allow first coat to dry 4-6 hours, then apply a second coat for a smooth, slip resistant surface. Floor is traffic ready in 24 hours.

Coverage: 300-500 square feet per gallon.

**DISPOSAL:** Dispose of contents/container to comply with local/regional/national/international regulations.



Please Recycle.

0124.021420