



DANGER

May be corrosive to metals. Causes severe skin burns and eye damage. May cause respiratory irritation.

Keep only in original container. Do not breathe mist, spray. Avoid breathing mist, spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection, protective clothing, protective gloves.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a doctor, a POISON CENTER if you feel unwell.

IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor, a POISON CENTER.

Absorb spillage to prevent material-damage.

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Store in corrosive resistant container with a resistant inner liner.

⚠️ WARNING: This product can expose you to 1,4-dioxane, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

NFPA® RATINGS

Health: 3; Flammability: 0; Reactivity: 0

CONTAINS/CAS NUMBER: Water/7732-18-5; Hydrochloric Acid/7647-01-0; Linear Alcohol Ethoxylate/34398-01-1; Tallow Alkyldiamine Ethoxylate/61790-85-0; Proprietary Surfactant/Proprietary; Acid Yellow 23/1934-21-0

*For industrial and commercial use only.
For additional information, see Safety Data Sheet.*

TOTAL SOLUTIONS®

POOL CARE

ACID “pH DOWN” ADJUSTMENT

- CONCENTRATE
- LOWERS pH WITHOUT CLOUDING WATER

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: One Gallon (128 fl. oz.)

Manufactured By: Total Solutions® • 1-800-743-6417
PO Box 240014 • Milwaukee, WI 53224 • athea.com

DESCRIPTION

This acid “pH-down” adjustment is the convenient liquid approach to lowering the pH of pool water or neutralizing alkalinity. It works quickly and effectively without clouding pool or spa water.

DIRECTIONS

The amount required to lower then pH depends on the water’s natural buffing capacity. Add 1 to 2 quarts directly to the pool at a point of strong agitation. Do not add to the skimmer or vacuum. Allow 15 to 20 minutes for thorough mixing, then retest the pH. Repeat treatment if needed.

DISPOSAL

Dispose of contents/container to comply with local/regional/national/international regulations.



Please Recycle.

0140.021720