

⚠️ WARNING: This product can expose you to ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

NFPA® RATINGS

Health: 1; Flammability: 0; Reactivity: 0

CONTAINS/CAS NUMBER:

Water/7732-18-5; Dimethicone/63148-62-9; Amodimethicone/68554-54-1;
Undeceth-5/34398-01-1; C9-11 Alcohols Ethoxylated/68439-46-3;
Cyclotetrasiloxane/556-67-2

TOTAL SOLUTIONS®

AUTOMOTIVE

PROTECT ALL

Protective Coating For
Vinyl, Leather, Plastic,
Wood, Metal, Rubber and
Many Other Surfaces

- CONDITIONS, BEAUTIFIES,
PROTECTS

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: One Gallon (128 fl. oz.)

Manufactured By: Total Solutions® • 1-800-743-6417
PO Box 240014 • Milwaukee, WI 53224 • athea.com

DESCRIPTION

This product is a premium silicone emulsion treatment that conditions surfaces and protects against checking, dulling, cracking, sun fading, hardening, deterioration and aging.

- Vinyl • Leather • Plastic • Rubber • Wood • Metal
- Chrome • Fiberglass • Cabinets • Counter Tops
- Appliances • Auto, Truck & Boat • Seats • Dash • Tires • Bumpers
- Weather Stripping • Household
- Institutional • Industrial • Virtually Any Surface!

It renews the original finish and restores a “like new” luster to most any surface, with anti-soil and anti-static agents to repel dirt and dust, to keep surfaces looking their best. Odorless, non-toxic and non-corrosive and contains no harmful solvents.

DIRECTIONS

Spray onto surface to be treated and spread evenly with a cloth. Allow to penetrate for several minutes then buff with a clean cloth. To renew weathered or damaged surfaces, three applications are recommended. Reapply as needed.

Do not use on or near clear plastic. Do not use on steering wheels, pedals, or other instrumentation where slipperiness may present a hazard.

DISPOSAL: Offer empty container for recycling. If recycling is not available, discard container in trash.



Please Recycle.

*For industrial and commercial use only.
For additional information, see Safety Data Sheet.*

0293.032724