

**DANGER**

May be fatal if swallowed and enters airways. May cause cancer.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective clothing, protective gloves.

IF SWALLOWED: Immediately call a doctor, a POISON CENTER, Do NOT induce vomiting. If exposed or concerned: Get medical advice/attention.

Store locked up.

NFPA® RATINGS

Health: 2; Flammability: 0; Reactivity: 0

CONTAINS/CAS NUMBER:

Hydrotreated Light Alkanes/64742-47-8; Alkanes, C14-16/90622-46-1; Barium Oxidate/68603-10-1; Barium Sulfonate/93820-55-4; Hydrotreated Heavy Alkanes/64742-52-5

TOTAL SOLUTIONS®

SPECIALTY PRODUCTS

MULTI-PURPOSE PENETRANT

Displaces and Seals
Out Moisture

- PENETRATES THREADS, CRACKS, AND JOINTS
- LUBRICATES METAL SURFACES

DESCRIPTION

This premium light lubricating oil is specially formulated for multi-purpose use by all municipal, industrial and institutional maintenance personnel. This labor saving product is indispensable for all mechanics, machinists, tool makers, pipefitters, assemblers and installers, plumbers and for all other maintenance functions.

- Saves production, maintenance and repair time.
- Protects and preserves valuable tools and equipment.
- Seals out moisture on mechanical and electrical equipment.
- Lubricates precision equipment. •Protects against corrosion.

DIRECTIONS

Generously apply this oil to all surfaces requiring protection by brushing, spraying, swabbing or dipping. Re-apply as needed when lubricating film is worn or weathered off.

DISPOSAL: Dispose of contents/container to comply with local/regional/national/international regulations.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: One Gallon (128 fl. oz.)

Manufactured By: Total Solutions® • 1-800-743-6417
PO Box 240014 • Milwaukee, WI 53224 • athea.com



Please Recycle.

*For industrial and commercial use only.
For additional information, see Safety Data Sheet.*

0300.021424