



DESCRIPTION

This ready-to-use cutting oil has special extreme pressure additives for extended tool life and increased production. It provides the high performance lubrication required for use with high carbon steels, stainless and other hard alloys as well as free machining steels.

Cutting and tapping oil clings to the cutting tool for excellent residual lubrication to make cleaner cuts, smoother finished surfaces and cooler tool temperatures. Ideal for use in all milling, boring, cutting, grinding, tapping, threading, sawing and other machining operations, this versatile oil allows better workpiece visibility and protection against rust.

This product is ready-to-use – do not dilute. Not recommended for use on copper or aluminum.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear eye protection, protective clothing, protective gloves.

If exposed or concerned: Get medical advice/attention.

Store locked up.

DISPOSAL: Dispose of contents/container to comply with local/regional/national/international regulations.

*For industrial and commercial use only.
For additional information, see Safety Data Sheet.*

TOTAL SOLUTIONS®

SPECIALTY PRODUCTS

CUTTING & TAPPING OIL

Ready to Use Coolant and Lubricant

- FOR DRILLING, TAPPING, CUTTING AND ALL MACHINING OPERATIONS

DANGER

May cause cancer.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: One Gallon (128 fl. oz.)

Manufactured By: Total Solutions®
PO Box 240014 • Milwaukee, WI 53224 • 1-800-743-6417

DIRECTIONS

Ready to use, no dilutions recommended.

NFPA® RATINGS

Health: 1; Flammability: 1; Reactivity: 0

CONTAINS/CAS NUMBER:

Solvent Refined, Hydrotreated Paraffinic Distillate/64742-54-7; Heavy Hydrotreated Naphthenic Distillates/64742-52-5



Please Recycle.

0301.052615