

Metalworking Coolant & Lube

Product # 303

Synthetic, dilutable concentrate

This water-dilutable coolant and lube is designed for use with all ferrous and non-ferrous metals in cutting, grinding, turning, and other

Use for:

- Cutting
- Grinding
- Drilling
- Tapping

Effective Against

- Corrosion
- Flash rusting
- Sticky residues
- Temperature build-up
- Wear & tear on machinery

Features and Benefits

- Protects finished work from flash rusting.
- Contains no silicon.
- When diluted it makes a clear solution.
- Dilution ratios can vary for the best economy under various conditions.
- Non-corrosive to all metals, including aluminum and copper.

Properties

Appearance	Golden brown liquid
Fragrance	Slight
Specific gravity	1.06
Flash point	>200° F
pH	9.5 – 10.2
Solubility	Complete in water

Directions *Complete directions on product label*

For severe operations and hard metals: Mix 1 part product into 10 parts of water.

For light duty operations: Mix one part product into 20 or 30 parts of water.

Ingredients

Water
Triethanolamine
Proprietary Ingredients
Diethanolamine
Benzisothiazolinone

CAS Number

7732-18-5
102-71-6
Not Available
111-42-2
2634-33-5

Safety

DANGER: Causes skin irritation. Causes serious eye damage. Suspected of causing cancer.

DOT Shipping (Ground Transportation)

Proper Shipping Name	None
Class	None
ID Number	None
Packing Group	None

Quantities

30, 35, & 55 gallon
5 or 6 gallon
6 x 1 gallon
4 x 1 gallon

NFPA® RATINGS

