

TOTAL SOLUTIONS®

SPECIALTY PRODUCTS

WELDING COOLANT GEL

Protects Heat Sensitive Surfaces

• CONCENTRATED COOLING GEL ABSORBS HEAT TO PROTECT SURFACES AND COMPONENTS WHILE SOLDERING, BRAZING OR WELDING

• GELS ON CONTACT FOR NO-DRIP COVERAGE

• ODORLESS, SKIN-SAFE, NON-TOXIC AND EASY CLEAN-UP

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: One Quart (32 fl. oz.)

Manufactured By: Total Solutions®
PO Box 240014 • Milwaukee, WI 53224
1-800-743-6417

DESCRIPTION

Welding Coolant Gel is an easy to use, gel barrier that shields surfaces from the intense heat generated during various welding operations. The viscous formula stays in place on surrounding surfaces made of metal, wood, wallboard, insulation, and other construction materials to protect them and prevent the transfer of heat beyond those surfaces.

⚠️ WARNING: This product can expose you to dichloromethane, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

DISPOSAL

Offer empty container for recycling. If recycling is not available, discard container in trash.

DIRECTIONS

Shake bottle before and during use as necessary. Spray or squeeze Welding Coolant Gel on surface immediately before applying heat source. If using trigger sprayer, make sure to use slow and steady trigger pulls or the sprayer may stop working. Be sure surface is completely covered and reapply as needed to complete job. If necessary, residue can be removed by wiping with a clean cloth.

NFPA® RATINGS

Health: 0; Flammability: 0; Reactivity: 0

CONTAINS/CAS NUMBER:

Water/7732-18-5; Polyacrylic Acid/9003-01-4; Sodium Hydroxide/1310-73-2; Sodium Chloride/7647-14-5; 2-methyl-2H-isothiazol-3-one/2682-20-4



Please Recycle.

*For industrial and commercial use only.
For additional information, see Safety Data Sheet.*

0312.032918