



## DESCRIPTION

Provides long-term protection even when exposed to steam, damp atmospheres, and salt spray. Protects metal parts under sustained temperatures up to 2100°F (1050°C). Dry lubricant acts as a sealant, reduces friction, makes tighter, firmer joints that open easier reducing torque requirements.

**USEFUL ON THESE SURFACES:**  
Cast Iron • Steel alloys • Aluminum  
Copper • Brass • Titanium  
Rubber - Natural and Synthetic

Keep away from heat, open flames, sparks. - No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof lighting, electrical equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear eye protection, protective clothing, protective gloves.

**IF SWALLOWED:** Immediately call a doctor, a POISON CENTER. Do NOT induce vomiting. **IF ON SKIN (OR HAIR):** Take off immediately all contaminated clothing. Rinse skin with water/shower.

**In case of fire:** Use carbon dioxide (CO<sub>2</sub>), dry extinguishing powder, foam to extinguish.

Store in a well-ventilated place. Keep cool. Store locked up.

*For industrial and commercial use only.  
For additional information, see Safety Data Sheet.*

# TOTAL SOLUTIONS®

SPECIALTY PRODUCTS

## GRAPHITE LUBRICANT

Extreme Temperature & Extreme Pressure Lubricant

- NON-MELTING
- NON-HARDENING

## DANGER

Flammable liquid and vapor.

May be fatal if swallowed and enters airways.

**KEEP OUT OF REACH OF CHILDREN**

**NET CONTENTS:** One Gallon (128 fl. oz.)

Manufactured By: Total Solutions®  
PO Box 240014 • Milwaukee, WI 53224 • 1-800-743-6417

## DIRECTIONS

Clean surface of oil, grease and dirt. Use with grease or gun pressure pump. Keep container tightly closed when not in use.

**⚠ WARNING:** This product can expose you to benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## DISPOSAL

Dispose of contents/container to comply with local/regional/national/international regulations.

## NFPA® RATINGS

Health: 2; Flammability: 2; Reactivity: 0

## CONTAINS/CAS NUMBER

Solvent Naphtha, Med. Aliphatic/64742-88-7; Distillates (Petroleum), Hydrotreated Light/64742-47-8; Alkanes C14-16/90622-46-1; Distillates (Petroleum) Hydrotreated Heavy Naphthenic/64742-52-5; Graphite/7782-42-5



Please Recycle.

0336.011718