

**DESCRIPTION**

This cationic polymer flocculent is designed for fast and efficient clarification of wastewater in industrial waste systems and municipal waste treatment facilities. It uses high molecular weight polymer for rapid settling of solids and suspended debris. This formula is easy to handle and dispense and will help to increase the waste-handling capacity of the system and reduce operating costs.

This biodegradable settling agent is nontoxic and will not harm fish or wildlife when used as directed. Typical applications include primary and secondary clarifier, digesters, settling ponds or basins and reservoirs.

Wash thoroughly after handling. Wear eye protection, protective clothing, protective gloves. Take off contaminated clothing and wash before reuse.

**IF ON SKIN:** Wash with plenty of water. **If skin irritation occurs:** Get medical advice/attention. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **If eye irritation persists:** Get medical advice/attention.

**DISPOSAL**

Offer empty container for recycling. If recycling is not available, discard container in trash.

*For industrial and commercial use only.  
For additional information, see Safety Data Sheet.*

# TOTAL SOLUTIONS®

WASTEWATER and  
SEWAGE TREATMENT

## SETTLING AGENT CONCENTRATE

CATIONIC POLYMER  
FLOCCULENT

- QUICKLY AND EFFECTIVELY  
PRECIPITATES SILT, CLAY,  
SLUDGE AND ORGANIC SOLIDS

**WARNING**

Causes skin irritation.

Causes eye irritation.

**KEEP OUT OF REACH OF CHILDREN**

**NET CONTENTS:** One Gallon (128 fl. oz.)

Manufactured By: Total Solutions®  
PO Box 240014 • Milwaukee, WI 53224 • 1-800-743-6417

**DIRECTIONS**

Feed this settling agent directly into the waste stream prior to the clarifier or settling basin. Drip or pump into the system at a point of strong agitation. Use rates may vary from 50 ppm up to 300 ppm (2 quarts up to 3 gallons per 10,000 gallons of waste). For maximum economy and effectiveness, continuous drip application is recommended.

For ponds or lagoons, drip or spray 10 to 20 gallons of settling agent per million gallons of water. Drip directly into waste stream or spray over surface to obtain even distribution of the polymer.

**NFPA® RATINGS**

Health: 1; Flammability: 0; Reactivity: 0

**CONTAINS/CAS NUMBER:**

Water/7732-18-5; Proprietary/Mixture



Please Recycle.

0384.050815