

**DANGER**

Causes skin irritation. Causes serious eye damage.

Wash thoroughly after handling. Wear eye protection, protective clothing, protective gloves. Take off contaminated clothing and wash it before reuse.

IF ON SKIN: Wash with plenty of water.

If skin irritation occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor.

⚠️ WARNING: This product can expose you to Ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

NFPA® RATINGS

Health: 1; Flammability: 0; Reactivity: 0

CONTAINS/CAS NUMBER:

Water/7732-18-5; C7-21 Alcohols Ethoxylated/68991-48-0; Sodium Metasilicate/6834-92-0; Pentasodium Triphosphate/7758-29-4; Ethoxylated Alcohols, Phosphate Ester/68130-47-2; Phosphoric Acid/7664-38-2; Sodium Hydroxide/1310-73-2

*For industrial and commercial use only.
For additional information, see Safety Data Sheet.*

TOTAL SOLUTIONS®

INDUSTRIAL CLEANERS
and DEGREASERS

BLAST

Designed for Oil-Water
Separators

- ALLOWS OIL AND GREASE TO SEPARATE AND BE REMOVED FROM RINSE WATER
- REDUCES ODORS
- REDUCES PUMP-OUTS

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: One Gallon (128 fl. oz.)

Manufactured By: Total Solutions® • 1-800-743-6417
PO Box 240014 • Milwaukee, WI 53224 • athea.com

DESCRIPTION

This concentrated cleaner and degreaser was designed to efficiently clean cars, trucks, and equipment. After removing greases and oils from equipment, it uses special surfactants to release the grease and oil that was just removed, letting go of them when the rinse water enters the oil-water separator. This allows for more efficient use of cleaner water, reduces the need to pump out the grey water tank, and reduces odors.

DIRECTIONS

Inject 2-8 ounces per gallon of water into the wash system. Wash trucks and equipment normally allowing the grey rinse water to collect through the oil-water separator. The oil and grease in the grey water will rise to the top of the oil-water separator where it can be skimmed off and removed.

DISPOSAL: Offer empty container for recycling. If recycling is not available, discard container in trash.



Please Recycle.

0414.092623