Safety Data Sheet



SECTION 1: Product and company identification

Product name : Enviro-Caustic™ Smokehouse Cleaner

Use of the substance/mixture : Cleaner Product code : 0433

Company : Total Solutions P.O. Box 240014

Milwaukee, WI 53224 - USA

T (414) 354-6417

Emergency number : Chemtrec: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Liq. 3 H226 Skin Corr. 1C H314

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)





GHS02

302 GHS05

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : Flammable liquid and vapor

Causes severe skin burns and eye damage

Precautionary statements (GHS-US) : Keep away from heat, open flames, sparks. - No smoking.

Keep container tightly closed.

Ground/Bond container and receiving equipment Use explosion-proof electrical, lighting equipment

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe mist, spray. Wash thoroughly after handling

Wear eye protection, protective clothing, protective gloves.

If swallowed: rinse mouth. Do NOT induce vomiting

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower

If inhaled: Remove person to fresh air and keep comfortable for breathing

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing

Immediately call a doctor, a POISON CENTER Specific treatment (see First aid measures on this label)

Wash contaminated clothing before reuse.

In case of fire: Use carbon dioxide (CO2), dry extinguishing powder, foam to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container to comply with local/regional/national/international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

Full text of H-phrases: see section 16

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Proprietary Caustic	(CAS-No.) Proprietary	1-5	Skin Corr. 1B, H314

Date of issue: 4/6/2018 Revision date: 04/06/2018 Version: 2.2 P GHS SDS Page 1 of 6

Safety Data Sheet



Name	Product identifier	%	GHS-US classification
Glycol Ether EB	(CAS-No.) 111-76-2	1-5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Asp. Tox. 1, H304
Sodium Tripolyphosphate	(CAS-No.) 7758-29-4	1-5	Not classified
SODIUM LAURETH SULFATE	(CAS-No.) 9004-82-4	1-5	Skin Irrit. 2, H315 Eve Dam. 1, H318

A specific chemical identity and/or percentage of composition has been withheld as a trade secret. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Get medical advice/attention if you feel unwell. Remove the victim into fresh air.

First-aid measures after skin contact : Rinse with water. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue

rinsing. Immediately call a poison center or doctor/physician.

First-aid measures after ingestion : Rinse mouth with water. Do NOT induce vomiting. Consult a doctor/medical service if you feel

unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Causes severe skin burns and eye damage.

Symptoms/effects after inhalation : None under normal use.

Symptoms/effects after skin contact : Caustic burns/corrosion of the skin.

Symptoms/effects after eye contact : Causes serious eye damage. Permanent eye damage.

Symptoms/effects after ingestion : Gastrointestinal complaints. Nausea. Vomiting. Cramps/uncontrolled muscular contractions.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : All extinguishing media allowed.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapor.

Reactivity : Upon combustion: CO and CO2 are formed. Reacts with (some) metals: release of highly flammable

gases/vapors (hydrogen).

5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed

containers. Take account of environmentally hazardous firefighting water.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Protective equipment : Protective goggles. Gloves. Protective clothing.

Emergency procedures : Evacuate unnecessary personnel. Avoid contact with skin, eyes and clothing. Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Stop leak if safe to do so. Stop release. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain released product, pump into suitable containers.

Methods for cleaning up : This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

No additional information available

Date of issue: 4/6/2018 Revision date: 04/06/2018 Version: 2.2 P GHS SDS Page 2 of 6

Safety Data Sheet



SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Comply with the legal requirements. Do not handle until all safety precautions have been read

and understood. Use personal protective equipment as required. Do not eat, drink or smoke

when using this product. Do not get in eyes, on skin, or on clothing.

Hygiene measures : Wash thoroughly after handling. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be

followed.

Storage conditions : Keep container closed when not in use. Keep only in original container.

Incompatible products : Oxidizing agent. Strong acids.

Incompatible materials : Sources of ignition.

Storage area : Meet the legal requirements. Store in a cool area. Store in a well-ventilated place.

Special rules on packaging : Keep only in original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Glycol Ether EB (111-76-2)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	Remark (ACGIH)	Eye & URT irr
OSHA	OSHA PEL (TWA) (mg/m³)	240 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	50 ppm

SODIUM LAURETH SULFATE (9004-82-4)

Not applicable

Sodium Tripolyphosphate (7758-29-4)

Not applicable

Proprietary Caustic (Proprietary)

Not applicable

8.2. Exposure controls

Personal protective equipment

Use appropriate personal protective equipment when risk assessment indicates this is necessary.
Gloves. Safety glasses. Protective clothing.







SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Clear, light yellow liquid.

Odor : Mild odor

Odor threshold : No data available

pH : > 12.5

Melting point : No data available Freezing point : No data available Boiling point No data available Flash point : 132 °F ASTM D3828 Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available **Explosion limits** : No data available Explosive properties No data available Oxidizing properties : No data available Vapor pressure : No data available : No data available Relative density

Date of issue: 4/6/2018 Revision date: 04/06/2018 Version: 2.2 P GHS SDS Page 3 of 6

Safety Data Sheet



Relative vapor density at 20 °C : No data available Specific gravity / density : 1.07 g/ml Solubility Soluble in water. Log Pow : No data available Log Kow : No data available Auto-ignition temperature No data available Decomposition temperature : No data available Viscosity No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available

VOC content : < 3.5

SECTION 10: Stability and reactivity

10.1. Reactivity

Upon combustion: CO and CO2 are formed. Reacts with (some) metals: release of highly flammable gases/vapors (hydrogen).

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

10.4. Conditions to avoid

No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Oxidizing agents. Strong acids.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Glycol Ether EB (111-76-2)	
LD50 oral rat	1300 mg/kg
LD50 dermal rat	> 2000 mg/kg
ATE CLP (oral)	1300 mg/kg body weight
ATE CLP (dermal)	1100 mg/kg body weight
ATE CLP (dust, mist)	1.5 mg/l/4h

Skin corrosion/irritation : Causes severe skin burns and eye damage.

pH: > 12.5

Serious eye damage/irritation : Not classified

pH: > 12.5

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified

Glycol Ether EB (111-76-2)

IARC group 3 - Not classifiable

Reproductive toxicity : Not classified Specific target organ toxicity – single exposure : Not classified Specific target organ toxicity – repeated : Not classified exposure

Chroat	Ethor.	ED	1444	76	21

Glycol Ether EB (111-76-2)	
NOAEL (oral,rat,90 days)	see comments
NOAEL (dermal,rat/rabbit,90 days)	see comments

Aspiration hazard : Not classified

Symptoms/effects after inhalation : None under normal use.

Symptoms/effects after skin contact : Caustic burns/corrosion of the skin.

Symptoms/effects after eye contact : Causes serious eye damage. Permanent eye damage.

Symptoms/effects after ingestion : Gastrointestinal complaints. Nausea. Vomiting. Cramps/uncontrolled muscular contractions.

Date of issue: 4/6/2018 Revision date: 04/06/2018 Version: 2.2 P GHS SDS Page 4 of 6

Safety Data Sheet

Likely routes of exposure : Skin and eye contact

SECTION 12: Ecological information

12.1. Toxicity

Glycol Ether EB (111-76-2) 1474 mg/l Oncorhynchus mykiss LC50 fish 1 EC50 Daphnia 1 100 mg/l Water flea ErC50 (algae) 1840 mg/l Pseudokirchneriella subcapitata NOEC chronic fish > 100 mg/l100 mg/l daphnid NOEC chronic crustacea

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container to comply with local/regional/national/international regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

Transport document description : UN1760 Corrosive liquids, n.o.s. (Calcium Hydroxide), 8, III

UN-No.(DOT) : UN1760

Proper Shipping Name (DOT) : Corrosive liquids, n.o.s.

: 8 - Class 8 - Corrosive material 49 CFR 173.136 Class (DOT)

Hazard labels (DOT) : 8 - Corrosive



Packing group (DOT) : III - Minor Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 203 DOT Packaging Bulk (49 CFR 173.xxx) : 241

DOT Symbols : G - Identifies PSN requiring a technical name

DOT Special Provisions (49 CFR 172.102) : IB3,T7,TP1,TP28

DOT Packaging Exceptions (49 CFR : 154

173.xxx)

DOT Quantity Limitations Passenger : 5 L

aircraft/rail (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft : 60 L

only (49 CFR 175.75)

DOT Vessel Stowage Location

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Additional information

Emergency Response Guide (ERG) : 154

Number

Other information When transported by ground, this product may be eligible to be shipped as a Limited Quantity or Consumer Commodity ORM-D utilizing the exception found at 49 CFR 173.154. If any alteration of

packaging, product, or mode of transportation is further intended, different shipping names and

labeling may be required.

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

Date of issue: 4/6/2018 Revision date: 04/06/2018 Version: 2.2 P GHS SDS Page 5 of 6

Safety Data Sheet



SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Glycol Ether EB	CAS-No. 111-76-2	1-5%

Glycol Ether EB (111-76-2)	
Subject to reporting requirements of United States SARA Section 313	

Sodium Tripolyphosphate (7758-29-4)	
Not subject to reporting requirements of the United States SARA Section 313	
CERCLA RQ	5000 lb

MWARNING

This product can expose you to ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H-phrases:

H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation


NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual

injury.

NFPA fire hazard : 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures

before ignition can occur.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.

Date of issue: 4/6/2018 Revision date: 04/06/2018 Version: 2.2 P GHS SDS Page 6 of 6