



DANGER

Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Avoid breathing mist, spray. Wash thoroughly after handling. Wear eye protection. In case of inadequate ventilation wear respiratory protection.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If experiencing respiratory symptoms: Call a doctor, a POISON CENTER.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

NFPA* RATINGS: Health: 2; Flammability: 0; Reactivity: 0

CONTAINS/CAS NUMBER: Water/7732-18-5; Propylene Glycol/57-55-6; Proprietary Surfactant/Mixture; Viable Bacterial Cultures/Mixture; Protease/9014-01-1

DISPOSAL

Dispose of contents/container to comply with local/regional/national/international regulations.

TOTAL SOLUTIONS®

BACTERIAL/ENZYME DIGESTANTS

LIQUIDASE™ 250

All-Purpose Digestant

- ALL-NATURAL BACTERIA
- SAFER TO USE
- BREAKS DOWN PROTEINS, STARCHES, CARBOHYDRATES, ANIMAL AND VEGETABLE DEPOSITS
- SALMONELLA FREE

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: One Quart (32 fl. oz.)

Manufactured By: Total Solutions®
PO Box 240014 • Milwaukee, WI 53224
1-800-743-6417 • athea.com

DESCRIPTION

This product contains a special blend of bacteria strains, both aerobic and facultative, chosen for their ability to digest and liquefy organic waste quickly, efficiently and without odors. The natural bacteria/enzymes break down proteins, starches, carbohydrates, and animal and vegetable deposits in drains and grease traps. Ideal for use in sinks, drains, urinals, toilets, grease traps, septic tanks, lift stations and sewer laterals. This product is the safer, more natural solution to keeping pipes clear of organic waste.

DIRECTIONS

SHAKE WELL BEFORE USING. DO NOT MIX WITH HOT WATER.

SINKS, FLOOR DRAINS, URINALS AND TOILETS: Use 2 ounces of digestant once per week in every drain and allow to work overnight. For drains that receive large amounts of organic matter (kitchen and floor drains, laundry sinks and drains), increase the treatment to 4-6 ounces, as often as every other day. For best results, treat at the end of day or other period of lowest flow. To prevent loosened debris from causing obstructions, always begin the treatment program by treating the lower floors first. Retreat after several hours. Do not mix with bleach, harsh drain openers or disinfectants.

GREASE TRAPS: For average size grease traps (about 20 cubic feet capacity), add 1 quart directly to trap or through drain. Then use 1 pint per week for maintenance.

SEPTIC TANKS: Use 2-4 quarts of this digestant for the initial treatment of 500 gallon tank. The weekly maintenance dose should be 1 pint for each 5 people using the system. Treat drain fields and leach beds by pouring directly into the distribution boxes or vents.

WET WELLS AND LIFT STATIONS: Add 1 quart per 500 cubic feet directly into wet well.

SEWER LATERALS: Laterals are treated during periods of low flow by adding through manholes. Dosage per unit length of lateral will vary with the diameter of the line:

LATERAL DIAMETER	OUNCES PER 500 FEET
8 INCHES	32 OUNCES
12 INCHES	48 OUNCES
16 INCHES	64 OUNCES
20 INCHES	96 OUNCES
24 INCHES	128 OUNCES

0534.021816



Please Recycle.

For industrial and commercial use only.
For additional information, see Safety Data Sheet.