



DANGER

Combustible liquid. May be fatal if swallowed and enters airways. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing cancer.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing dust/fume/gas/mist/ vapours/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

IF SWALLOWED: Immediately call a poison center or doctor. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. **If exposed or concerned:** Get medical advice/attention. Call a poison center or doctor if you feel unwell. Do NOT induce vomiting.

⚠ WARNING: This product can expose you to Cumene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

In case of fire: Use media other than water to extinguish.

Store in a well-ventilated place. Keep cool. Store locked up.

NFPA® RATINGS

Health: 2; Flammability: 2; Reactivity: 0

CONTAINS/CAS NUMBER: Hydrotreated Light Alkanes/64742-47-8; C9-15 Heavy Aromatic Hydrocarbons/64742-95-6; Butoxyethanol/111-76-2; Polyolefin alkyl phenol alkyl amine (2)/Proprietary; Trimethylbenzene/95-63-6; Cumene/98-82-8

*For industrial and commercial use only.
For additional information, see Safety Data Sheet.*

TOTAL SOLUTIONS®

AUTOMOTIVE

FUEL AID PLUS

Multi-Functional
Gasoline Additive

- REDUCES INTAKE VALVE, CARBURETOR, AND PORT FUEL INJECTOR DEPOSITS
- REDUCES EMISSIONS
- RUST AND CORROSION INHIBITOR OR PROTECTION FOR FUEL SYSTEMS
- GOOD WATER REMOVAL

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: One Gallon (128 fl. oz.)

Manufactured By: Total Solutions® • 1-800-743-6417
PO Box 240014 • Milwaukee, WI 53224 • athea.com

DESCRIPTION

This premium additive helps all types of gasoline powered engines run clean and more efficiently. Special detergents remove deposits and clogs from fuel injection systems for better acceleration, no stall, stumble, or run-on. Dispersant and corrosion inhibitor additives clean gums, varnish, and corrosion deposits from fuel tank, delivery system and carburetors – and protects from further corrosion. It extends engine life by eliminating intake valve deposits, and lubricating upper cylinders under cold start conditions.

This formula improves the performance of all gasoline powered engines, including those with catalytic converters and computer-controlled engines.

DIRECTIONS

Use 12 ounces for every 20 gallons of gasoline.
In bulk storage tanks, use 2 to 3 gallons per 1000 gallons of gasoline.

DISPOSAL

Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.



Please Recycle.

0649.100621