





DANGER

Highly flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness.

Keep away from heat, open flames, sparks. - No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical, lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist, spray, vapors. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eve protection, protective clothing, protective gloves.

IF SWALLOWED: Immediately call a doctor, a POISON CENTER, Do NOT induce vomiting.

IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention. Call a doctor, a POISON CENTER if you feel unwell.

In case of fire: Use carbon dioxide (CO2), dry extinguishing powder, foam to extinguish.

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

WARNING: This product can expose you to benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

NFPA® RATINGS

Health: 2; Flammability: 3; Reactivity: 0.

CONTAINS/CAS NUMBER:

Acetone/67-64-1: Heptanes/64742-49-0: Isopropanol/67-63-0

For industrial and commercial use only. For additional information, see Safety Data Sheet.



INDUSTRIAL CLEANERS and DEGREASERS

QUICK DRY SOLVENT CLEANER

Alternative to Chlorinated Solvents

DESCRIPTION

This product was developed to safely remove oil, grease, brake fluid, brake pad material or dirt from motor vehicle brake mechanisms.

DIRECTIONS

Dip brake parts to be cleaned into solvent. Allow to soak until soils are loosened. Remove and allow to dry.

DISPOSAL

Dispose of contents/container to comply with local/regional/national/international regulations

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: One Gallon (128 fl. oz.)

Manufactured By: Total Solutions[®] • 1-800-743-6417 PO Box 240014 • Milwaukee, WI 53224 • athea.com



1384.021318