



## DANGER

May cause an allergic skin reaction. Causes serious eye damage. Suspected of damaging fertility or the unborn child.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist, spray. Contaminated work clothing must not be allowed out of the workplace. Take off contaminated clothing and wash it before reuse. Wear eye protection, protective clothing, protective gloves.

**IF ON SKIN:** Wash with plenty of soap and water.

**If skin irritation or rash occurs:** Get medical advice/attention.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**If exposed or concerned:** Get medical advice/attention. Immediately call a doctor, a POISON CENTER.

Store locked up.

### NFPA\* RATINGS

Health: 2; Flammability: 0; Reactivity: 0

**CONTAINS/CAS NUMBER:** Water/7732-18-5; Nonoxynol/127087-87-0; Methoxydiglycol/111-77-3; Citrus Terpenes/94266-47-4; Methylisothiazolinone/2682-20-4

*For industrial and commercial use only.  
For additional information, see Safety Data Sheet.*

# TOTAL SOLUTIONS®

RESILIENT FLOOR CARE

## CRYSTAL IMAGE

### SPRAY-ON GLOSS RESTORER

- REACTIVE POLYMER MATRIX PRECISELY ADJUSTS TO MACHINE SPEED
- READY-TO-USE FORMULA

### KEEP OUT OF REACH OF CHILDREN

**NET CONTENTS:** One Gallon (128 fl. oz.)

Manufactured By: Total Solutions® • 1-800-743-6417  
PO Box 240014 • Milwaukee, WI 53224 • athea.com

### DESCRIPTION

This spray buff has been precisely formulated to match the composition of our floor finishes. Its unique Reactive Polymer Matrix (RPM) adjusts to machine speed and pad type to restore your finishes maximum gloss. Use as part of a regular spray buffing program to repair scratches and marks, enhance finish durability and extend finish life

### DIRECTIONS

Dry mop the entire floor with a treated dust mop to remove loose soil. If a heavy soil film remains after dry mopping, clean floor with a damp mop or an autoscrubber.

Apply a light mist of spray buff to the floor. Move buffing machine in a gentle side-to-side motion until floor appears dry and shiny.

### FLOOR CARE TIPS:

- Floors should be damp mopped regularly. Accumulated dust and dirt cause unsightly scratches or abrasion that will significantly reduce finish durability and lead to frequent stripping and recoating.
- Inspect pads frequently. If pads show an accumulation of old floor finish, dirt or accumulated restorer solution in the space between pad fibers, clean or replace immediately.
- Store damp pads in plastic bags between uses. Dried-out pads can scratch floors and require substantial amounts of spray buffing solution to become usable again.
- Spray buff a small area (approximately 5 foot x 5 foot) at a time, then move on to the next area.

### DISPOSAL

Dispose of contents/container to comply with local/regional/national/international regulations.



Please Recycle.

1714.110921