



DANGER

Causes skin irritation. Causes serious eye damage.

Wash thoroughly after handling. Wear eye protection, protective clothing, protective gloves. Take off contaminated clothing and wash it before reuse.

If on skin: Wash with plenty of water. **If skin irritation occurs:** Get medical advice/attention. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor, a POISON CENTER.

NFPA® RATINGS

Health: 2; Flammability: 0; Reactivity: 0

CONTAINS/CAS NUMBER:

Water/7732-18-5; Tripropylene Glycol Methyl Ether/25498-49-1; Ethanolamine/141-43-5; Trisodium Phosphate Dodecahydrate/10101-89-0; Cocamidopropyl Hydroxysultaine/68139-30-0

*For industrial and commercial use only.
For additional information, see Safety Data Sheet.*

TOTAL SOLUTIONS®

RESILIENT FLOOR CARE

CLEAR CUT

Non-ammoniated Wax Stripping Concentrate

- LOW ODOR FORMULA
- IDEAL FOR USE IN HEALTH CARE AND FOOD PREPARATION FACILITIES

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: One Gallon (128 fl. oz.)

Manufactured By: Total Solutions® • 1-800-743-6417
PO Box 240014 • Milwaukee, WI 53224 • athea.com

FLOOR CARE TIPS:

- Stripping solution should always be prepared just prior to use.
- Always dry mop before starting any stripping operation - Unremoved dirt and dust can damage floors during scrubbing operations.
- When scrubbing with a rotary scrubber, be certain to overlap passes to cover the entire floor. Walk only where you've scrubbed - It's less slippery.
- To prevent clogging, flip pads frequently. To keep pads in peak operating condition, clean with a dilute solution of stripper and store in a plastic bag.

DIRECTIONS

This stripper has been carefully formulated to be used as an integral part of scrub and rinse floor stripping program.

Dust mop entire floor to remove loose dust and dirt. Prepare a stripping solution by diluting 8 to 16 ounces of product per gallon of warm water. Recommended dilution rates are based upon floors with an accumulation of 10 coats of applied floor finish. To ensure proper solution strength, apply diluted product to a small area of floor. Flood floor with stripping solution with a wet mop. Allow the stripping solution to remain on the floor for 5 to 10 minutes.

Do not allow stripping solution to dry on floor. Scrub with a 175 - 300 rpm rotary floor machine equipped with a black stripping pad. If an autoscrubber is to be used, two passes are recommended to complete the scrubbing process. Pick up the stripping/finish residue with a wet vac or autoscrubber. To rinse, flood floor with clean cool water. Pick up with wet vac or autoscrubber. Complete rinsing process by damp mopping with clean, cool water and a clean mop.

DISPOSAL

Offer empty container for recycling. If recycling is not available, discard container in trash.



Please Recycle.

1718.090123