

# HEAVY DUTY PENETRATING OIL



## DANGER:

Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Suspected of causing cancer. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Store locked up. Protect from sunlight. Store in a well-ventilated place. Dispose of contents/container in accordance with local/regional/national/international regulations.

## FIRST AID:

**IF SWALLOWED:** Immediately call a poison center/doctor. Rinse mouth. Do not induce vomiting. **IF EXPOSED OR CONCERNED:** Get medical advice/attention. **IF INHALED:** If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.

## CONTAINS/CAS NUMBER:

Perchloroethylene (127-18-4), Kerosene (8008-20-6), Oil Additives (Proprietary) and Carbon Dioxide (124-38-9).

Distributed By: Total Solutions®  
PO Box 240014 • Milwaukee, WI 53224 • 1-800-743-6417

See Safety Data Sheet for complete safety information. 24 HOUR MEDICAL EMERGENCY 1-866-836-8855 CONTAINS NO OZONE DEPLETING CHEMICALS!



# TOTAL SOLUTIONS®

## SPECIALTY PRODUCTS

## HEAVY DUTY PENETRATING OIL

Non-Conducting Up  
To 45,000 Volts

- LUBRICATES
- CLEANS
- LOOSENS NUTS AND BOLTS
- HEAT STABLE - WILL NOT FREEZE OR MELT
- RETARDS CORROSION
- DISPLACES MOISTURE
- PENETRATES FASTER AND FARTHER

**KEEP OUT OF REACH OF CHILDREN**

**DANGER**

**VAPORS HARMFUL.**

**HARMFUL OR FATAL IF SWALLOWED.**

**EYE IRRITANT.**

**CONTENTS UNDER PRESSURE.**

Read carefully other cautions on back panel.

**NET WT: 20 OZ (1 lb 4 oz) 567 g**

Distributed By: Total Solutions®  
PO Box 240014 • Milwaukee, WI 53224 • 1-800-743-6417

## DESCRIPTION

FOR INSTITUTIONAL, COMMERCIAL AND INDUSTRIAL USE. NOT FOR SALE OR DISTRIBUTION IN CALIFORNIA

Saves production, maintenance, and repair time. Protects and preserves equipment. For use on refrigerator equipment, automobiles, work-shops. Frees nuts and bolts. Lubricates locks, hinges, moving parts. Stops and retards corrosion. Stops corrosion on battery terminals.

SPECIFICALLY DESIGNED TO PENETRATE DEEP TO FREE RUSTED AND CORRODED PARTS.

## DIRECTIONS

Remove cap and point valve opening toward surface to be sprayed. Hold can 4 - 8 inches away, push button and spray. Apply generously to surface to be treated. Repeat application when needed.

**Cautions:** Use with adequate ventilation. Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

**KEEP OUT OF REACH OF CHILDREN.**

## HMS® RATINGS:

HEALTH - \*2, FLAMMABILITY - 2, PHYSICAL HAZARD- 2, PERSONAL PROTECTION - X.