

SILICONE LUBE



DANGER: Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility. Suspected of damaging the unborn child. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 49°C / 120°F. Dispose of contents/container in accordance with local/regional/national/international regulations.

FIRST AID: IF SWALLOWED: Immediately call a poison center/doctor. Do NOT induce vomiting. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. **IF ON SKIN:** Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists. **IF EXPOSED OR CONCERNED:** Get medical advice/attention. Call a poison center/doctor if you feel unwell.

WARNING: This product can expose you to Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

CONTAINS/CAS NUMBER: Acetone (67-64-1), Butane (106-97-8), Propane (74-98-6), n-Heptane (142-82-5), Solvent naphtha (petroleum), light aliphatic (64742-89-8), Cyclohexane (110-82-7), n-Hexane (110-54-3) and Toluene (108-88-3).

Distributed By: Total Solutions®
PO Box 240014 • Milwaukee, WI 53224 • 1-800-743-6417

See Safety Data Sheet for complete safety information. 24 HOUR MEDICAL EMERGENCY 1-866-836-8855 CONTAINS NO OZONE DEPLETING CHEMICALS!

TOTAL SOLUTIONS®

SPECIALTY PRODUCTS

SILICONE LUBE

All Purpose Dry Lubricant Release Agent

- FOR COMMERCIAL AND INDUSTRIAL USE
- STOPS STICKING DRAWERS, WINDOWS, DOORS, SCREENS, ZIPPERS, LOCKS
- ELIMINATES ANNOYING SQUEAKS IN HINGES, LATCHES, SPRINGS
- HEAT STABLE - WILL NOT FREEZE OR MELT
- RETARDS CORROSION, PROTECTS BATTERY TERMINALS, TOOLS, GUNS, SKATES, ALUMINUM WINDOWS AND DOORS.
- FAST DRYING
- HELPS PREVENT GRASS, DIRT AND MUD FROM STICKING TO LAWN MOWERS - SNOW FROM STICKING TO SNOW SHOVELS

KEEP OUT OF REACH OF CHILDREN

DANGER

EXTREMELY FLAMMABLE.

HARMFUL OR FATAL IF SWALLOWED.

EYE AND SKIN IRRITANT.

CONTENTS UNDER PRESSURE.

Read carefully other cautions on back panel.

NET WT: 12 OZ (340 g)

Distributed By: Total Solutions®
PO Box 240014 • Milwaukee, WI 53224 • 1-800-743-6417

Use on any surface: metal, glass, rubber, plastic, painted finishes and fabrics.

USES:

Plastic Molding—Release agent for injection and compression moldings.

Packaging—Prevents waxes, adhesives and plastics from sticking to heat sealer bars. Reduces clean-up time. Eliminates friction on guide rails, line conveyors, scramble tables, etc.

Converters and Printers—Eliminates glue build-up on working surfaces. Reduces friction on paper cutters, knives, drills, etc.

Industrial—For industrial blenders, bins, conveyors, paper, leather, textile and paper mill dry cans, plating screens, glass, fiber, fabric, hosiery forms, container coating for easy release of sticky contents.

Automotive—Lubricates window channels, door, weather stripping, trunk seals, under-carriage, rubber mounting, emergency brakes, pedal shafts, car seats, adjustment mechanisms. Eliminates squeaks from fan belts (do not apply when running). Prevents battery terminal corrosion. Waterproofs ignition system, hinges, springs and casters.

Garment—Promotes slip on sewing machine beds, cutting tables and dies. Prevents bunching of fabrics during sewing operation.

DIRECTIONS

Thoroughly clean the surface to be sprayed. Spray a light film with a sweep motion. When used on sticking surfaces work object back and forth. Spray again if necessary.

Cautions: Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Prolonged inhalation may be harmful. Use with adequate ventilation.

KEEP OUT OF REACH OF CHILDREN.

HMS® RATINGS:

HEALTH - *2, FLAMMABILITY - 4, PHYSICAL HAZARD - 2, PERSONAL PROTECTION - X.