

BASEBOARD STRIPPER



DANGER:

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear eye protection/face protection. Wear protective gloves. Protect from sunlight. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 49°C/120°F. Dispose of contents/container in accordance with local/regional/national/international regulations.

FIRST AID:

IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash before reuse. If skin irritation or rash occurs: Get medical advice/attention. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. **IF INHALED:** Move to fresh air. Call a physician if symptoms develop or persist. **IF SWALLOWED:** Not likely, due to the form of the product. In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.

CONTAINS/CAS NUMBER:

Aqua (7732-18-5), Butoxyethanol (111-76-2), Butane (106-97-8), Propane (74-98-6), Phosphated mono/diglyceride, sodium salt (208539-94-0) and Sodium Hydroxide (11310-73-2). For more ingredient information visit the website or call the phone number on this label.

Distributed By: Total Solutions®

PO Box 240014 • Milwaukee, WI 53224 • 1-800-743-6417

See Safety Data Sheet for complete safety information. 24 HOUR MEDICAL EMERGENCY 1-866-836-8855 CONTAINS NO OZONE DEPLETING CHEMICALS!

TOTAL SOLUTIONS®

RESILIENT FLOOR CARE

BASEBOARD STRIPPER

Removes Heavy Wax Build-UP in Hard to Reach Areas

- FLOORS, BASEBOARDS, CERAMIC WALL TILE
- CLINGING FOAM ADHERES TO SURFACES
- EASY RINSING
- USE IN UPSIDE DOWN POSITION

KEEP OUT OF REACH OF CHILDREN

CAUTION

MAY CAUSE EYE AND SKIN IRRITATION.

CONTENTS UNDER PRESSURE.

Read carefully other cautions on back panel.

NET WT: 19 OZ (1 lb. 3 oz.) 539 g

Distributed By: Total Solutions® • 1-800-743-6417
PO Box 240014 • Milwaukee, WI 53224 • athea.com

DESCRIPTION

Use to remove wax build-up from baseboards, floors and ceramic wall tiles.

DIRECTIONS

SHAKE WELL BEFORE USING.

Check the product on a small inconspicuous area of the surface to be sprayed to make sure there is no attack. Do not spray on painted or varnished surfaces. Wipe off any overspray immediately.

Turn can UPSIDE DOWN and hold 6-10 inches from baseboard or surface to be sprayed. A thin even coating should cover the wax.

Wait 3 to 5 minutes, longer in case of substantial build-up. Wet scrub the surface with an abrasive pad or scrub brush. Repeat until all wax is removed.

Rinse surface with clean water and allow area to dry thoroughly before re-polishing.

Cautions: Use with adequate ventilation. Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

KEEP OUT OF REACH OF CHILDREN.

HMIS® RATINGS:

HEALTH - 2, FLAMMABILITY - 2
PHYSICAL HAZARD - 2, PERSONAL PROTECTION - X.